


REV.	ECN NO.	DESCRIPTION	DRAW	APPD	DATE
A	---				



受控文件

Specification:
 Current rating: 1,5PIN 1.8A Max/2,3,4PIN 1A Max.
 Dielectric withstanding voltage: 100 V(ac) for 1 min.
 Contact resistance: 30 mΩ Max.
 Insulation resistance: 100 MΩ Min.
 Total mating force: 3.57 Kgf Max.
 Total unmating force: 1.0 Kgf Min.
 Temperature range: -30°C~80°C

深圳市兴烨电子有限公司
 Shenzhen XingYe Electronics co., Ltd

Series Name :		
Product Description :	MICRO-5P立贴平口无柱不锈钢加盖编带	
Part NO:	MKF26136	
SCALE	SHEET	REV.
1:1	1/1	A1

No.	Pare Name	Number	Material	Remarks
3	Shell	1PCS	SUS304	t=0.25mm
2	Contacts	5PCS	copper alloy	t=0.20mm
1	Housing	1PCS	LCP	UL94v-0

TOLERANCE					
X.X	±0.30	X.°	±2°	APPD:	陈爱光
.XX	±0.20	.X.°	±1°	CHED:	施立敏
.XXX	±0.10	.XX.°	±0.5°	DRAW:	马洪飞
UNITS		mm			